

## SITECONT

This is a flexible hose made of austenitic stainless steel. It is so flexible that this feature protects the hose against breaking when masonry settles. Sitecont makes it easier to install the gas meter, which is usually to be placed in very narrow spaces. All the parts in contact with gas in the GCONT003/4/5/6/7 models are made of austenitic stainless steel, and the hose is adjustable.

Sitecont may be manufactured to meet our customers' specific length requirements.



**Application:** connections for gas meters.

**Operating pressure:** limited to 0.5 bar.

**Test:** helium leak detector spectrometer; test value: 1x10<sup>-6</sup> mbar l/s.

Item	Length	Fittings G1	Description	Fittings G2	Description
	mm		Fittings G1		Fittings G2
GCONT001	150	F 3/4" Fixed	Nickel plated steel	F 1" Revolving	brass OT 58
GCONT002	170	F 3/4" Fixed	Nickel plated steel	F 1" 1/4 Revolving	brass OT 58
GCONT025	250	F 1" Fixed	Nickel plated steel	F 1" 1/4 Revolving	brass OT 58
GCONT003	200	M 3/4" Fixed	Austenitic stainless steel	F 1" 1/4 Revolving	brass OT 58
GCONT004	250	M 3/4" Fixed	Austenitic stainless steel	F 1" 1/4 Revolving	brass OT 58
GCONT005	200	M 1" Fixed	Austenitic stainless steel	F 1" 1/4 Revolving	brass OT 58
GCONT006	250	M 1" Fixed	Austenitic stainless steel	F 1" 1/4 Revolving	brass OT 58
GCONT007	200	M 1" 1/2 Fixed	Austenitic stainless steel	F 2" Revolving	brass OT 58