

SITEGAS DN12

Sitegas DN12 is a flexible hose made of austenitic stainless steel and manufactured according to the highest quality standards. The sheath protects the flexible hose against corrosion caused by deposits of chlorides, cleansing agents or any other substances that can generally found in a domestic environment.



EN 14800:2007

Application: connection of domestic appliances (fixed and built-in cooktops) using natural gas, manufactured gas and LPG.

Test: helium leak detector spectrometer; test value: 1x10⁻⁶ mbar l/s.


Fittings: supplied: female/female or female/male.

Lengths: 500 - 750 - 1000 - 1250 - 1500 - 2000 mm.

Operating pressure: limited to 0.5 bar complying with the regulations in force that set the use of devices with nominal heat appliances not exceeding 35 kW.

Range of operating temperature: -40 °C +60 °C

Minimum bending radius: 1.5 times the outside diameter of the hose.



Hose: corrugated continuous-wall; the fittings and the braid are made of austenitic stainless steel.

Cover: sheath made of plastic.

Item code	DN	Length	Fittings
	mm	mm	
GFN150506	12	500	F 1/2" - F 1/2"
GFN150756	12	750	F 1/2" - F 1/2"
GFN151006	12	1000	F 1/2" - F 1/2"
GFN151256	12	1250	F 1/2" - F 1/2"
GFN151506	12	1500	F 1/2" - F 1/2"
GFN152006	12	2000	F 1/2" - F 1/2"
GMN150506	12	500	M 1/2" - F 1/2"
GMN150756	12	750	M 1/2" - F 1/2"
GMN151006	12	1000	M 1/2" - F 1/2"
GMN151256	12	1250	M 1/2" - F 1/2"
GMN151506	12	1500	M 1/2" - F 1/2"
GMN152006	12	2000	M 1/2" - F 1/2"